

QUICKSTRAPS™ FASTENERS



PRODUCT DESCRIPTION

Ideal Products' QuickStraps™ are cut to length straps manufactured from various types of materials including Aluminum, T304, T316, and Galvanized Steel. QuickStraps™ are fabricated using automated processes and innovative technologies. QuickStraps™ are designed to decrease installation times and reduce the need for any onsite fabrication.

PRODUCT APPLICATION

QuickStraps™ can be used on a variety of applications for fastening including heat tracing, electrical wiring, insulation, and cladding. Available types are the Insulstrap and Fabstrap. Each type of strap is recommended for use on their specific applications.

QUICKSTRAPS™ INSULSTRAPS are designed for quickly securing various types of insulation, but not limited to heat tracing systems and various other applications. The self-locking mechanism on the female end ensures a safe and quick install. Insulstraps can be applied by hand and do not require any special tools depending on the application. Insulstraps can also be applied using Ideal Products unique all-in-one applicator that tightens and cuts the excess material when required (See application tools for further information). Insulstraps are manufactured with rounded male and female ends for safe handling.

QUICKSTRAPS™ FABSTRAPS are designed for securing various types of cladding and insulation, but not limited to heat tracing systems and various other applications. Fabstraps come with an attached wing seal, and precision cut to various lengths of 100+ sizes for a custom fit to most pipe and insulation diameter combinations. Fabstraps are applied with most commonly used tension and cutting tools.

PRODUCT COMPLIANCE

QUICKSTRAPS™ INSULSTRAP

| STANDARD | MATERIAL | COMPLIANCE |
|-----------|-----------------------|------------|
| ASTM A240 | T304, T316 | Conforms |
| ASTM A123 | Galvanized Mild Steel | Conforms |

QUICKSTRAPS™ FABSTRAPS

| STANDARD | MATERIAL | COMPLIANCE |
|-----------|-------------------|------------|
| ASTM A240 | T304, T316 | Conforms |
| ASTM B209 | Aluminum H14 3003 | Conforms |

MATERIAL SPECIFICATIONS

QUICKSTRAPS™ INSULSTRAP

| | |
|------------------|---|
| MATERIAL | T304, T316, Mild Steel Galvanized |
| FINISHES | BA |
| WIDTHS | 0.47" |
| GAUGES | 0.010" |
| SIZES | 35", 45", 55", 65", 75", 85", 95", 105", 115", 125", 135", 145", 155" |
| TENSILE STRENGTH | 1200N (270 LBS) |

QUICKSTRAPS™ FABSTRAP

| | |
|----------|--|
| MATERIAL | Aluminum, T304, T316 |
| FINISHES | BA, 2B |
| WIDTHS | 0.5", 0.75" |
| GAUGES | Aluminum: 0.020" / T304 & T316: 0.015", 0.020" |
| SIZES | Cut to length according to pipe and insulation dimensions. See sizing chart. |

Safer. Smarter. Faster.

